

Contactors

CWB Series

Accessories and Spare Parts

Front Mounted Auxiliary Contact Blocks⁴⁾



.063 kg

For use with	Max. n° of additional contacts / contactor	Auxiliary contacts		Catalog Number	List Price	Multiplier
		NO	NC			
CWB9...38	4 / CWB9...38 4 / CWB40...80 4 / CWB00...2	1	1	BFB-11 ¹⁾	\$20	Z1
		2	0	BFB-20	\$20	
		0	2	BFB-02 ¹⁾	\$20	
		2	2	BFB-22 ¹⁾	\$32	
		2	2	BFB-22 EL ³⁾	\$32	
		4	0	BFB-40	\$32	
		0	4	BFB-04 ¹⁾	\$32	
		3	1	BFB-31 ¹⁾	\$32	
1	3	BFB-13 ¹⁾	\$32			

Side Mounted Auxiliary Contact Blocks⁴⁾



.034 kg

For use with	Max. n° of additional contacts / contactor	Auxiliary contacts		Catalog Number	List Price	Multiplier
		NO	NC			
CWB9...38	4 / CWB9...38 4 / CWB40...80 4 / CWB00...2	1	1	BLB-11 ¹⁾	\$22	Z1
		2	0	BLB-20		
		0	2	BLB-02 ¹⁾		
		1	1	BLRB-11 ¹⁾²⁾		
		2	0	BLRB-20 ²⁾		
		0	2	BLRB-02 ¹⁾²⁾		

Plug-In Surge Suppressors



.008 kg

For use with	Voltage	Diagram	Catalog Number	List Price	Multiplier	
CWB9...38 CWB40...80 CWB00...2	24...48 V 50/60 Hz		RCB-D53	\$30	Z1	
	50...127 V 50/60 Hz		RCB-D55			
	130...250 V 50/60 Hz		RCB-D63			
	12...48 V 50/60 Hz / 12...60 V dc		VRB-E49			
	50...127 V 50/60 Hz / 60...180 V dc		VRB-E34			
	130...250 V 50/60 Hz / 180...300 V dc		VRB-E50			
	277...380 V 50/60 Hz / 300...510 V dc		VRB-E41			
	400...510 V 50/60 Hz		VRB-D73			
	12...600 V dc					DIB-C33
	12...250 V dc					DIZB-C26

Notes: 1) The arrangement of the contacts meets IEC 60947-4-1 Annex F (Mirror Contact) and IEC 60947-5-1 Annex L (Mechanically Linked Contact) requirements.

2) For combination of 2 side-mounted auxiliary contact blocks at the same side of the contactor.

3) BFB-22-EL: besides the regular contacts NO and NC, there are two special contacts: early make and late break.

4) The maximum number of auxiliary contacts assembled on the contactor are 4.