

Selection Table

Three-Pole CWB Contactors from 9 A to 80 A (AC-3)

le máx. (Ue ≤440 V)	le = lth (Ue ≤690 V) θ ≤55 °C	Maximum UL Horsepower						Built-in auxiliary contacts per contactor		Catalog Number	List Price AC Coil	List Price DC Coil	Multiplier
		Single Phase		Three Phase									
		115V	230V	200V	230V	480V	575V						
AC-3 A	AC-1 A												
9	25	3/4	1.5	3	3	5	7 1/2	1	1	CWB9-11-30*	\$72	\$118	Z1
12	25	3/4	2	3	3	7 1/2	10	1	1	CWB12-11-30*	\$89	\$123	
18	32	1	3	5	5	10	15	1	1	CWB18-11-30*	\$103	\$150	
25	40	2	5	7 1/2	7 1/2	15	15	1	1	CWB25-11-30*	\$118	\$177	
32	50	3	5	10	10	20	25	1	1	CWB32-11-30*	\$140	\$220	
38	50	3	7.5	10	10	25	25	1	1	CWB38-11-30*	\$164	\$282	
40	60	3	7 1/2	10	15	30	30	1	1	CWB40-11-30*	\$164	\$282	
50	90	3	10	15	15	40	40	1	1	CWB50-11-30*	\$225	\$310	
65	110	5	10	20	20	50	50	1	1	CWB65-11-30*	\$255	\$350	
80	110	7 1/2	15	20	25	50	60	1	1	CWB80-11-30*	\$270	\$417	

Three-Pole CWB NEMA Rated Sizes 00 - 2

le máx. (Ue ≤440 V)	le = lth (Ue ≤690 V) θ ≤55 °C	Maximum UL Horsepower						Built-in auxiliary contacts per contactor		Catalog Number	List Price AC Coil	List Price DC Coil	Multiplier
		Single Phase		Three Phase									
		115V	230V	200V	230V	480V	575V						
AC-3 A	AC-1 A												
9	25	4-Mar	1 1/2	3	3	5	7 1/2	1	1	CWBN00-11-30*	\$103	\$150	Z1
18	32	1	3	5	5	10	15	1	1	CWBN0-11-30*	\$118	\$177	
25	40	2	5	7 1/2	7 1/2	15	15	1	1	CWBN1-11-30*	\$164	\$220	
50	90	3	10	15	15	40	40	1	1	CWBN2-11-30*	\$233	\$330	

Replace “♦” by the appropriate coil voltage code³⁾.

Alternating Current

Code	D02	D07	D15	D77	D25	D33	D39	D45	V24
V (50/60 Hz)	24	48	120	208	240	380	480	600	208-254v

Direct Current

Code	C03	C07	C09	C12	C13	C15
V dc	24	48	60	110	125	220

Notes: 1) Orientative values.

2) Weight for contactors with control circuit in alternate current. For control circuit in direct current, add 0.121 kg to the alternating-current models.

3) Other voltages on request.